

BUC-KU40-10.75 + IP CTRL



BUC-Ku40-10.75 + IP Ctrl

40 W () 46 dBm () 10.75 GHz.
sat

BUC 10 MHz

ALC -9 . P +4 dB
ALC

+ **LED** .

- : PBR120
- (): 40
- LO : 8.8 9.75 10.6 10.75 10.8 11.3 11.8 12.8 13.05 ()
- : 800-1000 Ku (10-15)
- : 950 – 1750 (950-1950)
- (): 71
-
- LO PLL
- IMD3 ALC (): -37
- 20
- : 32APSK

:	
	950 – 1750 MHz (950-1950 MHz)
	50 Ohm

	-15 dBm
VSWR	1.5
	N-type Female
ALC	25 dB
:	
LO	10750 MHz ()
LO:	
@1 kHz	-80 dBc/Hz
@10 kHz	-85dBc/Hz
@100 kHz	-100dBc/Hz
LO	± 2ppm
:	
	11700 – 12500 MHz ()
sat P	46 dBm
ALC P	36 dBm*
ALC ()	-9 ... +4 dB from P _{ALC}
	72 dB
IMD3	ALC-37 dBc
	Waveguide WR75, Flange PBR120
VSWR	2
:	

	± 1.5 dB
:	
sat P	-55 dBc
	-30 dBm
LO ALC	-40 dBm
	60 dB
:	
	20 VDC – 55 VDC, nominal 48 VDC
	< 100 W
:	
IF	N-type female
RF	WR75 (PBR120)
DC	C90-3102R10SL-4P
	UTS014E19P
	ALC Ethernet
LED	<ul style="list-style-type: none"> – OK – MUTE – AGC –
:	
	-30 to +55
	-40 to +70

	100%, non-condensing
:	
	260x135x92 mm
	5 kg

(UMT LLC)

!

/