

سبيلتك في رل وحم 5.85-6.725 GHZ | 400W ة رقب C ق لظلل SSPB



SSPB C 400W 5.85-6.725 GHz 75 dB
MHz

RF مئطخ		
		400 W
RF	Psat	56 dBm
RF	Plin	53 dBm
		C
		5.85-6.725 GHz
		950–1825 MHz
		4.90 GHz
		-55 dBc
		-30 dBc @ Plinear
IMD		-25 dBc

	75 dB
	20 dB 0.1 dB
	±2.0 dB
	±2.0 dB ; ±0.5 dB 40 MHz

رہلال ا عطیہ و عجمہل ا	
10 MHz	0 dBm ±5 dB
	-63 dBc/Hz @100 Hz; -73 dBc/Hz @1 kHz

ت اہج اہل ا	
	50
VSWR	1.50:1
RF	CPR 137G ()
IF	N-Type 50
	: MS3102R14S-9P; : MS3102R14S-7P; : MS3112E1419P; : MS3112E14-19S ()

ق ہلال ا	
(AC)	1500 W

تقنيون لئىمل لىرىطرخل ا	
(L×W×H)	139 × 298 × 489 mm
	26 kg

تقنييىل لىرىطرخل ا	
	-40...+55 °C
	-40...+75 °C
	0–100% ()
	10,000

(UMT LLC)

!هلاخ لم