


DRA-KU150



DRA-Ku150 is Double Reflector Antenna (Cassegrain antenna).

It is designed for Ku-band: 10-15 GHz

Supports linear and circular polarizations (by order)

Beam (H): 0.9°; Beam (V): 0.9°

Cross-polarization isolation: 25 dB

Gain: 41 dBi

| Specification | |
|---|--------------------|
| Frequency range, GHz | 10 – 15 |
| Gain, dBi | 41 |
| VSWR | 2 |
| Polarization | Linear or circular |
| Cross-polarization isolation, dB | 25 |
| HPBW: | |
| @horizontal | 0.9° |

| | |
|--|--|
| @vertical | 0.9° |
| Side-lobe level relative to the main beam, dB | |
| Input power, W | 20 |
| Waveguide | WR-75 or C-120 |
| Temperature range, °C | -50 to +80 |
| Humidity | 100% where 25°C |
| Size, mm | |
| Weight, kg | |
| Mount | Mounting on a vertical pipe with a diameter of 50-100 mm |
| Casing material | Canvas coverage |

Taking into consideration that we (UMT LLC) are developer and system integrator, also do not stop on our technical growth and improvement, know that view of all our devices and equipment including their technical parameters may be different from pictures presented on website and parameters

listed on each device webpage.

Note! All details customer has to confirm in advance during ordering and before payment. Those parameters that were not specified and / or were not agreed while ordering will be implemented as basic at the discretion of the manufacturer. Each our customer has 1.5 year warranty and 7 year aftersales support for whole range of our products.