

DVB-C 8-ASI SCRAMBLER



DVB-C 8-ASI Scrambler is professional solution for multichannel digital video broadcasting: it is broadcasting server with own memory and integrated multiplexer, scrambler and modulator (up to 4 carriers), all in one, powerful conditional access system

Inputs/Outputs	
Input Interface	8xDVB-ASI inputs; 1xIP input
Output Interface	2xDVB-ASI outputs, 1xRF output, 1x100M IP output
Modulation parameters	
Frequency Range	36-900 MHz
Modulation Type	QAM; constellation 32/64/128/256
Output Signal Bandwidth	less 8 MHz
Adjustable Symbol Rate	1-6.9 Msym/s, 1 ksym/s step
Output RF Signal Level	80-100 dBuV, adjustment -10 dBuV
IP stream	
IP	RTP, UDP protocol support
Power Supply	

Power	~220V+-20%
Power Consumption	Max 18 W
Others	
Size	19", 1U 480×45×180 (mm)
Weight	3.5 Kg

Taking into consideration that we (UMT LLC) are developer and system integrator, also do not stop on our technical growth and improvement, know that view of all our devices and equipment including their technical parameters may be different from pictures presented on website and parameters

listed on each device webpage.

Note! *All details customer has to confirm in advance during ordering and before payment. Those parameters that were not specified and / or were not agreed while ordering will be implemented as basic at the discretion of the manufacturer. Each our customer has 1.5 year warranty and 7 year aftersales support for whole range of our products.*