

DVB-T MODULATOR



Multichannel DVB-T/T2 modulator is developed special for professional TV broadcasting. It supports modulations **from QPSK to 64-QAM** with high modulation error rate (MER) **more than 27 dB**.

Inputs		
Interface, connector type	RF, N-type (F or SMA as option)	
RF Output:		
RFout (50)	80-100 dBμV	
Number of inputs, connector type	RF output N-type (F or SMA as option)	
Injection	Optionaly can provide injection of DC and 10 MHz reference	
Modulation parameters DVB-T mode:		
Constellation	QAM16 / QAM32 / QAM64	
Modulation Error Rate (MER)	>40 dB	
FEC	1/2 , 2/3 , 3/4 , 5/6 , 7/8	
Symbolrate	_	
Bandwidth	5, 6, 7, 8 MHz	
Signals injection		

10 MHz reference	10 ⁻⁶ -10 ⁻⁸ stability (optionally)
Power injection	for the BUC 24V, 3A (optionally)
Adjustment	
Interface	RJ-45, Ethernet
Power Supply	
Input Voltage	110-240 V AC, 50/60 Hz
Power Consumption	6W per channel
Environmental	
Operating Temperature	0 to 45 (32 to 113)
Storage Temperature	-20 to 80 (-4 to 176)
Operating Humidity	90%, non-condensing
Mechanical Mechanical	
Dimensions (W x H x D)	1RU: 483mm x 44.5mm x 450mm, 19" x 1.73" (1RU) x 17.7" 2RU: 483mm x 89mm x 450mm, 19" x 3.5" (2RU) x 17.7"

Taking into consideration that we (UMT LLC) are developer and system integrator, also do not stop on our technical growth and improvement, know that view of all our devices and equipment including their technical parameters may be different from pictures presented on website and parameters

listed on each device webpage.

Note! All details customer has to confirm in advance during ordering and before payment. Those parameters that were not specified and / or were not agreed while ordering will be implemented as basic at the discretion of the manufacturer. Each our customer has 1.5 year warranty and 7 year aftersales support for whole range of our products.