

HD + ASI



HD + ASI + IP
AVC / H.264 (HD/SD) 4 IP + 2 ASI.

	4xXLR, 1xHDMI, 2xSDI
	2xSDI 2xCVBS, 2xHDMI 2xASI
:	
	1080i@60; 1080i @59.94; 1080i @50; 576i @50; 480i @59.94
	MPEG-2 HD/SD; MPEG-4 AVC/H.264 HD/SD
	1Mbps~15Mbps (0.5 Mbps~15Mbps)
	CBR/VBR
GOP	IPB, IBBP, IPPP
	SD – 4:3; 16:9; HD -16:9
	4:2:0
	2 ASI, 1 10/100 Base-T Ethernet

:	
	1920×1080, 1440×1080, 960×1080, 720×1080, 1280×704, 1280×768, 1024×768, 720×576, 704×576, 544×576, 480×576, 720×480, 704×480, 640×480, 544×480, 480×480, 480×256, 320×224, 240×180
	MPEG-2/H.264; H264/MPEG-2 (H.264/H.264; MPEG-2/MPEG-2)
	0.5 -15 Mbps
	4:3; 16:9
:	
	MPEG-1 Layer II, +6/-6.7 db
	48kHz
	24-bit
	64Kbps~384Kbps
	1 (100ms ())
	2× ASI BNC
	4xIP, MPTS/SPTS over UDP/RTP, 10/100 Base-T Ethernet interface (UDP/RTP multicast/unicast) Rj45 interface
	-
	AC 220V±10%, 50Hz
	17W

(WxDxH)	440mm×190mm×44mm
	3.5kg

(UMT LLC) ！