


## LNB PLL LO 10.75



Ku-band LNB PLL LO 10.75 is Low Noise Block Down Converter with single LO 10.75 GHz and single 75 Ohm F-type output. LO instability:  $\pm 150$  kHz, Gain: 45 dB, Noise figure: 0.9 dB, Output power P1dB: +3 dBm.

Input parameters:	
Input Frequency range	11.70 – 12.70 GHz
Input level, max	-57 dBm
Input VSWR, max	2.0
Input interface	Waveguide WR75, Flange PBR120
Local Oscillator:	
LO frequency	10.75 GHz
LO Phase noise:	
@1 kHz	-75 dBc/Hz
@10 kHz	-85 dBc/Hz
@100 kHz	-95 dBc/Hz
LO instability	$\pm 150$ kHz

**Output parameters:**

<b>Output frequency range</b>	950 – 1950 (or by order)
<b>Output Power @P1dB</b>	+3 dBm
<b>Gain, min</b>	45 dB
<b>Output interface</b>	F-type female
<b>Output impedance</b>	75 Ohm
<b>Output VSWR, max</b>	2.5

**Frequency Response:**

<b>Flatness over Full Band</b>	±2 dB
<b>Flatness over 27MHz Band</b>	±0.75 dB

**Spurious:**

<b>Noise Figure (@+25 )</b>	0.9 dB max
<b>LO leakage, max</b>	-45 dBm
<b>Image rejection, min</b>	45 dBc

**Power supply:**

<b>Input voltage</b>	12 VDC – 24 VDC, nominal 18 VDC
<b>Power consumption, max</b>	5.25 W

**Environmental:**

<b>Operating temperature</b>	-30 to +60 (-22 to +140 )
<b>Storage temperature</b>	-40 to +80 (-40 to +176 )
<b>Operating humidity</b>	0% – 95%

### Mechanical:

<b>Dimensions (W x H x D)</b>	60x42x126 mm
<b>Weight</b>	0.4 kg

*Taking into consideration that we (UMT LLC) are developer and system integrator, also do not stop on our technical growth and improvement, know that view of all our devices and equipment including their technical parameters may be different from pictures presented on website and parameters*

*listed on each device webpage.*

**Note!** *All details customer has to confirm in advance during ordering and before payment. Those parameters that were not specified and / or were not agreed while ordering will be implemented as basic at the discretion of the manufacturer. Each our customer has 1.5 year warranty and 7 year aftersales support for whole range of our products.*