


LNB PLL LO 8.80



LNB Ku PLL LO 8.80

(LNB)

8.80 GHz

P1dB: +3 dBm.

| | |
|----------|-------------------------------|
| : | |
| | 9.75 – 10.75 GHz |
| | -57 dBm |
| VSWR | 2.0 |
| | Waveguide WR75, Flange PBR120 |
| : | |
| LO | 8.80 GHz |
| LO: | |
| @1 kHz | -75 dBc/Hz |
| @10 kHz | -85 dBc/Hz |
| @100 kHz | -95 dBc/Hz |
| LO | ± 150 kHz |
| : | |

| | |
|---------|---------------------------------|
| | 950 – 1950 (or by order) |
| P1dB | +3 dBm |
| | 45 dB |
| | F-type female |
| | 75 Ohm |
| VSWR | 2.5 |
| : | |
| | ±2 dB |
| 27MHz | ±0.75 dB |
| : | |
| (@+25) | 0.9 dB max |
| LO | -45 dBm |
| | 45 dBc |
| : | |
| | 12 VDC – 24 VDC, nominal 18 VDC |
| | 5.25 W |
| : | |
| | -30 to +60 (-22 to +140) |
| | -40 to +80 (-40 to +176) |
| | 0% – 95% |
| : | |

| | |
|-------------|--------------|
| (W x H x D) | 60x42x126 mm |
| | 0.4 kg |

(UMT LLC)

!

/