STB-UMT-S265-MINI



STB-UMT-S265-mini (STB receiver **DVB-S/DVB-S2 MPEG-2/MPEG-4/H.264/HEVC/H.265** **CA**.

STB-UMT-S265-mini :

- Fully DVB-S/DVB-S2/MPEG-2/MPEG-4/H.264/HEVC/H.265 compliant
- CVBS/RGB/YPbPr/HDMI/Scart output supported,USB 2.0 port PVR, multi-media player
- SCPC & MCPC receivable from C/Ku band satellites
- DiSEqC 1.0/1.1/1.2/1.3(USALS) supported
- Universal LNB, NIT search support
- Electronic program guide (EPG) , VBI Teletext,Supports up to 64 satellites
- Up to 2,500 transponders, Frequency range: 950 … 2150 MHz
- Auto/Manual Program search, Multi-language supported
- USB 2.0 for PVR, Timeshift, Software upgrade, Multimeida Playback,OTA software upgrade
- Transmission mode: LDPC/BCH (DVB-S2) 8PSK/QPSK, DVB-S QPSK
- Support up to 5000 channels
- Support up full HD 1080P,HDMI 1.3
- Support Multi CAS
- Support multi-TS stream

DVB-S2	
	950MHz to 2150MHz

	75Ohms unbalanced
	-65 ~ -25dBm
	2-45Mbps
LNB	13/18V,Max 350mA
	47-862 MHz
	QPSK/8PSK
	FEC 1/2,2/3,3/4,5/6,7/8,8/9,9/10
SDRAM	1Gbit DDR3
FLASH	64Mbit FLASH
	ISO/IEC 13818-2 and ISO/IEC 14496-10
	ISO/IEC 13818-1
	HEVC/H.265,MPEG-4 H.264/AVC SD/HD,MPEG-2 SD/HD (MP@ML and MP@HL),
	JPEG,BMP,PNG, Motion JPEG
	AVI, VOB, MOV, MKV
	480i, 480p, 576i, 576p, 720p, 1080i, 1080p
	4:3, 16:9 Auto

	MPEG-1 Layer I & II, MPEG-2 Layer II, AAC, MP3, HE-AAC,AC-3(optional), E-AC-3(optional)
	32, 44.1, 48
Teletext	
	DVB Subtitle
HDMI	HDMI version 1.3
LNB	IEC169-2 Female
USB	2
RS232	1
CVBS & R/L	RCA(1 ports)
IR	LED IR
	IR 38kHz NEC
	1
RCA	1(Optional)
HDMI	1(Optional)
DC	12V/1.5A(Optional)
	Max 18W

	0 ~ 45 °C

(UMT LLC)

!هظح لم

. /