

STB-UMT-ST265-MINI



STB-UMT-ST265-mini ()
 H.265 CA.

STB-UMT-ST265-mini :

- AVL2569L chipset Solution with high sensitive tuner
- Fully DVB-S2/T2/ISDB-T and ITU-TJ.83A/B/C compliant
- CVBS/HDMI output supported,USB 2.0 port PVR, multi-media player
- Support MPEG-1,MPEG-2 ,MPEG-4,H.264/HEVC/H.265 HD decoder
- Advanced audio processor supporting Dolby Digital and Dolby Digital Plus(optional)
- USB2.0 host support upgrade ,PVR,timeshifting and media play with U-Flash or HDD
- Frequency Range:55-862MHz

DVB-T2	
	VHF&UHF
	COFDM(QPSK/QAM16/QAM64) QAM : 16/32/64/128QAM
	7 8
RF	(bypass)IEC 169-2 Male
	177.5-226.5MHz(VHF),474-858 MHz(UHF)

DVB-S2	
	950 to 2150Mhz
	-79 to-11dbm
	1 to 45M
	75
DVB-S2	
	64/16/4QAM
	QPSK,8PSK,16APSK,32APSK
	1/2,2/3,3/4,5/6,7/8,8/9,9/10
SDRAM	1GBit
FLASH	64MBit Flash
	ISO/IEC 13818-2 and ISO/IEC 14496-10
	ISO/IEC 13818-1
	HEVC/H.265,MPEG-4 H.264/AVC SD/HD,MPEG-2 SD/HD (MP@ML and MP@HL),
	JPEG,BMP,PNG, Motion JPEG
	AVI, VOB, MOV, MKV
	480i, 480p, 576i, 576p, 720p, 1080i, 1080p
	4:3, 16:9 Auto

	MPEG-1 ,MPEG-2(Layer I & II),MP3,AAC-LC 5.1, HE-AAC v1/v2,AC-3(optional), E-AC-3(optional)
	32, 44.1, 48
EPG	
Teletext	
DVB	
LCN (Nordig v1)	
Mhz)	NIT S21 (306
	LCN
	/
OTA USB	(DSM-CC)
	...
LED	()
LED	/ STB
	3

LNB IN	IEC169-2 Female
ANT IN	ISO/IEC 13818-1
	R/L RCA
USB	USB2.0 interface*2pcs
LAN	1
	IR 38kHz NEC
LED	1pcs
	1
RCA	1(Optional)
HDMI	1(Optional)
DC	12V/1A
	Max 12W
	0 ~ 45 °C

(UMT LLC)

!

/