C-BAND SSPB 1000W 5.725–6.425 GHZ SOLID STATE POWER BUC

High-power C-band SSPB 1000W, out freq. 5.725–6.425 GHz, 80 dB gain, low phase noise, solid-state linear design with forced-air cooling. Ideal for teleports, gateways, and broadcast satcom uplinks. Psat 60 dBm, LO 4.75 GHz, IF 975–1675 MHz.

RF Characteristics	
Power	1000 W
RF Output at Psat	60 dBm
RF Output at Plin	57 dBm
Output Frequency Range	5.725–6.425 GHz
Input Frequency Range	975–1675 MHz
Local Oscillator Frequency	4.75 GHz
Output Spurious	-55 dBc max
Spectral Re-growth	-30 dBc @ Plinear
Third order IMD	-25 dBc
Gain & Linearity	
Linear Gain	80 dB Nominal
Gain Control	20 dB in 0.1 dB steps

Gain Stability Over Temp	±2.0 dB max
Gain Variation at fixed temp	±2.0 dB over full band; ±0.5 dB over 40 MHz
Reference & Phase Noise	
10 MHz Reference	0 dBm ±5 dB
Phase Noise	-83 dBc/Hz @10 kHz; -93 dBc/Hz @100 kHz
Interfaces	
Input Impedance	50 Ohms
Output VSWR	1.50:1
RF Output Interface	CPR 137G (Grooved)
IF Input	N-Type Female, 50 Ohms
Connectors	DC: MS3102R14S-9P; AC: MS3102R14S-7P; M&C: MS3112E1419P; Redundancy: MS3112E14-19S (Optional)
Power & Cooling	
Cooling	Forced Air
Mechanical	
Dimensions (L×W×H)	195 × 406 × 565 mm
Weight	50 kg
Environmental	
Operating Temperature	-40…+55 °C

Storage Temperature	-40…+75 °C
Humidity	0—100% (condensing)
Altitude	10,000 ft ASL

Taking into consideration that we (UMT LLC) are developer and system integrator, also do not stop on our technical growth and improvement, know that view of all our devices and equipment including their technical parameters may be different from pictures presented on website and parameters listed on each device webpage.

Note! All details customer has to confirm in advance during ordering and before payment. Those parameters that were not specified and / or were not agreed while ordering will be implemented as basic at the discretion of the manufacturer. Each our customer has 1.5 year warranty and 7 year aftersales support for whole range of our products.