



## C-BAND SSPB 200W 5.725–6.425 GHZ SOLID STATE POWER BUC

High-power C-band SSPB 200W, out freq. 5.725–6.425 GHz, 70 dB gain, low phase noise, and solid-state linear design. Ideal for VSAT hubs, gateways, and broadcast satcom uplinks. Psat 53 dBm, LO 4.75 GHz, IF range 950–1675 MHz.

RF Characteristics	
Power	200 W
RF Output at Psat	53 dBm
RF Output at Plin	50 dBm
Output Frequency Range	5.725–6.425 GHz
Input Frequency Range	950–1675 MHz
Local Oscillator Frequency	4.75 GHz
Output Spurious	-55 dBc max
Spectral Re-growth	-30 dBc @ Plinear
Third order IMD	-25 dBc
Gain & Linearity	
Linear Gain	70 dB Nominal
Gain Control	20 dB in 0.1 dB steps

Gain Stability Over Temp	$\pm 2.0$ dB max
Gain Variation at fixed temp	$\pm 2.0$ dB over full band; $\pm 0.5$ dB over 40 MHz
<b>Reference &amp; Phase Noise</b>	
10 MHz Reference	0 dBm $\pm 5$ dB
Phase Noise	-83 dBc/Hz @10 kHz; -93 dBc/Hz @100 kHz
<b>Interfaces</b>	
Input Impedance	50 Ohms
Output VSWR	1.50:1
RF Output Interface	CPR 137G (Grooved)
IF Input	N-Type Female, 50 Ohms
Connectors	DC: MS3102R14S-9P; AC: MS3102R14S-7P; M&C: MS3112E1419P; Redundancy: MS3112E14-19S (Optional)
<b>Power &amp; Cooling</b>	
Cooling	Forced Air
<b>Mechanical</b>	
Dimensions (LxWxH)	187 x 197 x 317 mm
Weight	13.6 kg
<b>Environmental</b>	
Operating Temperature	-40...+55 °C

Storage Temperature	-40...+75 °C
Humidity	0–100% (condensing)
Altitude	10,000 ft ASL

*Taking into consideration that we (UMT LLC) are developer and system integrator, also do not stop on our technical growth and improvement, know that view of all our devices and equipment including their technical parameters may be different from pictures presented on website and parameters listed on each device webpage.*

**Note!** *All details customer has to confirm in advance during ordering and before payment. Those parameters that were not specified and / or were not agreed while ordering will be implemented as basic at the discretion of the manufacturer. Each our customer has 1.5 year warranty and 7 year aftersales support for whole range of our products.*