

CONDITIONAL-ACCESS MODULE (CAM) CARDLESS



Conditional Access Module (CAM) – Cardless DVCrypt CI Module for Encrypted Digital TV Access

The CAM is Conditional Access Module of the DVCrypt scrambling system with common conditional access interface (Common Interface) in TVs and digital television receivers. CAM allows to provide subscribers with access to encrypted content in digital television.

The CAM supports DVCrypt video content scrambling system.

CAM is made in the PCMCIA form factor.

The CAM is equipped with slot for installation of smart cards ([Subscriber CAS cards](#)).

General characteristics	
Conditional Access System	DVCrypt
Compatibility	All TVs and STBs with CI or CI+ slots
Usage	DVB-S/S2, DVB-T/T2, DVB-C environments
Physical characteristics	
Form Factor	PCMCIA Type II
Dimensions	<ul style="list-style-type: none"> • 100 x 58 x 5 mm (Length x Width x Depth) • 86 x 54 x 5 mm

Connector	68-pin PCMCIA
Interface protocols	
Common Interface Protocols	according to profile 1 DVB-CI protocol and PCMCIA specifications
Smart Card Interface	<ul style="list-style-type: none"> • built-in smartcard reader • ISO7816 standard • cardless version available
Electrical characteristics	
Operating Voltage	3 ~ 5V

Taking into consideration that we (UMT LLC) are developer and system integrator, also do not stop on our technical growth and improvement, know that view of all our devices and equipment including their technical parameters may be different from pictures presented on website and parameters listed on each device webpage.

Note! All details customer has to confirm in advance during ordering and before payment. Those parameters that were not specified and / or were not agreed while ordering will be implemented as basic at the discretion of the manufacturer. Each our customer has 1.5 year warranty and 7 year aftersales support for whole range of our products.