



## DVB-S/S2 REGENERATOR V2.0



### DVB-S/S2 Regenerator – Multichannel Signal Recovery Device by UMT LLC

The **DVB Regenerator** by **UMT LLC** is a professional-grade multichannel device designed to restore and retransmit **noisy or weakened DVB-S/S2 signals**. Supporting up to **32 independent regeneration channels**, this unit ensures **clean signal recovery** and consistent output for **satellite TV broadcasting, MVDS, and headend systems**.

Controlled via Ethernet using **UMT's proprietary VCC software**, the regenerator is available with **F-type, N-type, or SMA connectors** to suit your setup. Designed for high reliability, it features **built-in protections** against overvoltage, overload, and short circuits. If power is lost, all settings are safely recovered on restart.

Inputs	
The input level	-65 ... -25 dBm
RF Frequency range (DVB-S/S2)	950 MHz-2150 MHz in 1 kHz-steps
Interface, connector type	RF, N-type (F or SMA as option)

<b>Symbol rate</b>	<p>1 ... 45 MSymb/s (<u>QPSK</u>);</p> <p>1 ... 45 MSymb/s (<u>8PSK</u>);</p> <p>1 ... 38.7 MSymb/s (<u>16PSK</u>, 1 channel mode),</p> <p>1 ... 43 MSymb/s (<u>16PSK</u>, 1 channel mode, <u>by request</u>);</p> <p>1 ... 31 MSymb/s (<u>32PSK</u>, 1 channel mode),</p> <p>1 ... 34.5 MSymb/s (<u>32PSK</u>, 1 channel mode, <u>by request</u>);</p> <p>in steps of 1 KSymb/s</p>
<b>RF output</b>	
<b>RF out (50 )</b>	80-100 dBμV
<b>Number of inputs, connector type</b>	RF output N-type (F or SMA as option)
<b>Injection</b>	Optionaly can provide injection of DC and 10 MHz reference
<b>RF Frequency range (DVB-S/S2)</b>	950 MHz-2150 MHz in 1 kHz-steps
<b>Modulation parameters DVB-S mode</b>	
<b>Constellation</b>	QPSK
<b>Modulation Error Rate (MER)</b>	>27 dB
<b>FEC</b>	1/2 , 2/3 , 3/4 , 5/6 , 7/8
<b>Symbolrate</b>	1–45 MSymbol/s
<b>Bandwidth</b>	defined by symbolrate
<b>Modulation parameters DVB-S2 mode</b>	

<b>Constellation</b>	QPSK / 8PSK / 16APSK or 32APSK (by request)
<b>Modulation Error Rate (MER)</b>	>27 dB
<b>FEC (LDPC)</b>	1/4 , 1/3 , 2/5 , 1/2 , 3/5 , 2/3 , 3/4 , 4/5 , 5/6 , 8/9 , 9/10
<b>Symbolrate</b>	1 ... 45 MSymb/s ( <u>QPSK</u> ); 1 ... 45 MSymb/s ( <u>8PSK</u> ); 1 ... 38.7 MSymb/s ( <u>16PSK</u> , 1 channel mode), 1 ... 43 MSymb/s ( <u>16PSK</u> , 1 channel mode, <u>by request</u> ); 1 ... 31 MSymb/s ( <u>32PSK</u> , 1 channel mode), 1 ... 34.5 MSymb/s ( <u>32PSK</u> , 1 channel mode, <u>by request</u> ); in steps of 1 KSymb/s
<b>Roll-Off-Factor</b>	0.2, 0.25, 0.35
<b>Pilots</b>	on/off
<b>Bandwidth</b>	defined by symbolrate
<b>Signals injection</b>	
<b>10 MHz reference</b>	$10^{-6}$ - $10^{-8}$ stability (optionally)
<b>Power injection</b>	for the BUC 24V, 3A (optionally)
<b>Adjustment</b>	
<b>Interface</b>	RJ-45, Ethernet
<b>Power Supply</b>	
<b>Input Voltage</b>	110-240 VAC, 50/60Hz

<b>Power Consumption</b>	6W per channel
<b>Environmental</b>	
<b>Operating Temperature</b>	0 to 45 (32 to 113 )
<b>Storage Temperature</b>	-20 to 80 (-4 to 176 )
<b>Operating Humidity</b>	90%, non-condensing
<b>Mechanical</b>	
<b>Dimensions (W x H x D)</b>	1RU: 483mm x 44.5mm x 450mm, 19'' x 1.73'' (1RU) x 17.7'' 2RU: 483mm x 89mm x 450mm, 19'' x 3.5'' (2RU) x 17.7''

*Taking into consideration that we (UMT LLC) are developer and system integrator, also do not stop on our technical growth and improvement, know that view of all our devices and equipment including their technical parameters may be different from pictures presented on website and parameters listed on each device webpage.*

**Note!** *All details customer has to confirm in advance during ordering and before payment. Those parameters that were not specified and / or were not agreed while ordering will be implemented as basic at the discretion of the manufacturer. Each our customer has 1.5 year warranty and 7 year aftersales support for whole range of our products.*