

16-HD ENCODER



16-HD Encoder is professional HD audio / video encoding and multiplexing device with integrated **ASI** outputs. **16 HDMI** inputs support **MPEG-4 AVC / H.264 / H.265** standards. **16-HD Encoder** can be used both for IP TV (**IP** output MPTS / SPTS) and as a part of head-end station.

| Inputs | |
|----------------------------------|--|
| Number of channels, interface | 16, HDMI |
| Video | |
| Input video resolution | 1920×1080p 60, 1920×1080p 50 (by request) 1920×1080i 60, 1920×1080i 50 1280×720p 60, 1280×720p 50 720×576i 50, 720×480i 59.95 480×360p |
| Video encoding | MPEG-4 AVC/H.264 Baseline/Main/High Profile HEVC/H.265 High Profile |
| Bit rate modes | CBR/VBR/ABR |
| Video bit rate range per channel | 0.5-40 Mbit/s |
| GOP structure | IPPP |
| Pre-processing | de-interlacing, 3D noise reduction, sharpening, anti-flicker for output videos and graphics |

| Audio | |
|----------------------------------|---|
| Audio encoding: | MPEG-1 Layer 2, LC-AAC, HE-AAC, AC3, EAC3 |
| Audio bit rate range per channel | HE-AAC: 32-128 kbit/s; MP2: 34-384 kbit/s; LC-AAC: 64-256 kbit/s; AC3: 64-384 kbit/s; EAC3: 64-384 kbit/s |
| Audio gain | 0-200% |
| Multiplexing | |
| Multiplexing processing | PSI/SI insertion and editing PCR correction PID remapping and passing through |
| Outputs | |
| Number of ASI outputs, connector | 2, BNC-type |
| IP output channels, connector | 1 channel MPTS and 16 channels SPTS, 1000base-T Ethernet interface (unicast/multicast) |
| Supply | |
| Supply voltage, power | AC 100...220V±10%, 50/60Hz, up to 50W |

Taking into consideration that we (UMT LLC) are developer and system integrator, also do not stop on our technical growth and improvement, know that view of all our devices and equipment including their technical parameters may be different from pictures presented on website and parameters

listed on each device webpage.

Note! All details customer has to confirm in advance during ordering and before payment. Those parameters that were not specified and / or were not agreed while ordering will be implemented as basic at the discretion of the manufacturer. Each our customer has 1.5 year warranty and 7 year aftersales support for whole range of our products.