

8-CHANNEL COMBINER-EQUALIZER



8-channel combiner-equalizer is active device designed to combine 8 independent IF carriers (L-band) in the frequency range of 950-2150 MHz with power adjustment and AGC for each channel.

Inputs / Outputs	
Number of inputs, connector type	8 x F-type, Female, 75 (N-type, Female, 50 – optional)
Output, connector type	1 x F-type, Female, 75 (N-type, Female, 50 – optional)
AUX Output (-20 dB), connector type	1 x F-type, Female, 75 (N-type, Female, 50 – optional)
General parameters:	
A working range of frequencies, MHz	950 – 2150
VSWR inputs/outputs, no more than	1.6
Gain flatness	5 dB
The range of power level adjustment into each of channels, dBm	-37 ... -7
The Maximum level of the input modulated signal, dBm, no more than	-10

The maximum total output power of the modulated signals on OUT sockets, dBm, no more than	0
Power Supply	
Input Voltage	110-240 VAC, 50/60Hz
Power Consumption	
Environmental	
Operating Temperature	0 to 45 (32 to 113)
Storage Temperature	-20 to 80 (-4 to 176)
Operating Humidity	90%, non-condensing
Mechanical	
Dimensions (W x H x D)	1RU: transport mode: 450mm x 45mm x 240mm operating mode: 49cm x 45mm x 270mm
Weight	1RU: * Kg

Taking into consideration that we (UMT LLC) are developer and system integrator, also do not stop on our technical growth and improvement, know that view of all our devices and equipment including their technical parameters may be different from pictures presented on website and parameters

listed on each device webpage.

Note! All details customer has to confirm in advance during ordering and before payment. Those parameters that were not specified and / or were not agreed while ordering will be implemented as basic at the discretion of the manufacturer. Each our customer has 1.5 year warranty and 7 year aftersales support for whole range of our products.