

BUC-KU02-9.75 V2.0



BUC-Ku02-9.75 v2.0 is block up-converter with fixed output power P1dB **2 W** (ALC power: 200 mW) and LO of **9.75 GHz**.

Our BUC operates with up to 25 carriers and has built-in reference of 10 MHz;

and ALC with 25 dB range;

IP Ctrl (by order)

+ LED status indication at the rear side.

Input parameters:		
Input frequency range	950 – 1950 MHz	
Input impedance	50 Ohm	
Input level, max	-12 dBm	
Input VSWR, max	1.5	
Input interface	N-type Female	
ALC range, min	25 dB	
ALC threshold level	-30 dBm	

Local oscilator:

LO frequency	9750 MHz	
LO phase noise:		
@1 kHz	-80 dBc/Hz	
@10 kHz	-85 dBc/Hz	
@100 kHz	-100 dBc/Hz	
LO instability	± 2 ppm	
Output parameters:		
Output frequency range	10700 — 11700 MHz	
Output power @P1dB	2 W	
ALC output power	200 mW	
Gain, min	53 dB	
IMD3 level at ALC output power, max	-37 dBc	
Output interface	Waveguide WR75, Flange PBR120	
Output VSWR, max	2	
Frequency response:		
Flatness over Full Band	± 1.5 dB	
Spurious:		
In-band @P1dB, max	-55 dBc	
Out-Band, max	-30 dBm	
LO leakage at ALC output power, max	-40 dBm	
Image rejection, min	60 dB	

Power supply:	
Input voltage	18 — 30 VDC, nominal 24 VDC
Power consumption, max	15 W
Environmental:	
Operating temperature	-40 to +50 (-40 to +122)
Storage temperature	-60 to +80 (-76 to +176)
Operating humidity	100%, non-condensing
Mechanical:	
Dimensions (W x H x D)	104x89x157 mm
Weight	1.15kg

Taking into consideration that we (UMT LLC) are developer and system integrator, also do not stop on our technical growth and improvement, know that view of all our devices and equipment including their technical parameters may be different from pictures presented on website and parameters

listed on each device webpage.

Note! All details customer has to confirm in advance during ordering and before payment. Those parameters that were not specified and / or were not agreed while ordering will be implemented as basic at the discretion of the manufacturer. Each our customer has 1.5 year warranty and 7 year aftersales support for whole range of our products.