



RE-MULTIPLEXEUR DVB-8TS



Destiné à l'intégration de services provenant de 8 entrées ASI indépendantes et prépare les flux de transport pour une modulation DVB-C / T / T2 / S / S2 / S2x ultérieure.

- analyse des flux de transport d'entrée, y compris les flux élémentaires (PID, tables, etc.) ;
- obtenir le PID en mode automatique ou manuel à partir des flux d'entrée et autres flux élémentaires avec possibilité de modifier les flux ;
- multiplexage des flux dans un flux de transport multiprogramme ;
- multiplexage de flux non codés et codés ;
- mesure de la vitesse du flux ;
- mode d'analyse détaillée des flux d'entrée ;
- génération et modification de toutes les tables de service (traitement SI et PSI) pour le flux spécifié ;
- édition des descriptions de programmes ;
- Correction PCR pour tous les programmes du flux cible ;
- des tables (TOT et TDT) générées en temps réel ;
- installation flexible en fonction des vitesses du flux de sortie ;
- indication de la présence du signal à chaque entrée ;
- indication de débordement du tampon du multiplexeur ;
- insertion d'une table d'informations sur le réseau (NIT) ;
- gestion et surveillance via LAN et Internet ;
- insertion d'un guide électronique des programmes (EPG) (option supplémentaire) ;
- Téléchargement EPG depuis hmltv – fichier ;
- prise en charge multilingue ;
- longueur de description du programme de 3,8 Ko ;

- Le nom du programme peut contenir jusqu'à 240 caractères.
- contenu de multiplexage et de distribution
- MVDS, LMDS, MMDS, MITRIS
- Tête de tête
- Lien TV
- Répéteur TV

Input/Output	
Input standard	DVB ASI
Mode	packet, byte
Package lenght	188/204
Determination of the type input stream	automatic
Quantity of input ports	8
Input connector type	BNC
Input voltage	200..880 mV
Input resistance	75 Ohm
Input bit-rate	to 216 Mb/s
Amount filtered elementary stream on each input	to 256
Output standard	DVB ASI
Quantity of output ports	2
Output connector type	BNC
Output voltage	800 mV
Output resistance	75 Ohm

Output bit-rate	to 216 Mb/s
The step of the installation to output velocity	1 b/s
Mode	packet, byte
Package lenght	188/204
The amount service in output transport stream	to 128
Amounts elementary stream in output stream	to 8191
Intervals of the measurement of the velocities stream	from 1 seconds to 1 week

Indicators, key field, display to front panel of management

The indicators	conditions of the system
Key field, display to front panel of management (optional)	image of the condition of the system and deskside

DVB-ASI TS Re-Multiplexer Form factor

Form factor	1RU (19)
Size	44mm x 482mm x 240mm
Voltage	88..264 In variable current
Frequency of the current	47..63 Hz
The Worker temperature	from 0C to +50C
Operating humidity	80%, non-condensing

Taking into consideration that we (UMT LLC) are developer and system integrator, also do not stop on our technical growth and improvement, know that view of all our devices and equipment including their technical parameters may be different from pictures presented on website and parameters listed on each device webpage.

Note! All details customer has to confirm in advance during ordering and before payment. Those

parameters that were not specified and / or were not agreed while ordering will be implemented as basic at the discretion of the manufacturer. Each our customer has 1.5 year warranty and 7 year aftersales support for whole range of our products.