

## SWA-KU360 V2 11.7-12.7 GHZ



SWA-Ku360v2 11.7-12.7 GHz is omni Slotted Waveguide Antenna

It is designed for Ku-band with antenna aperture of 360° and H-polarization

Frequency range of 11.7-12.7 GHz (or other 800 MHz of Ku-band)

Beam (H): 360°; Beam (V): 10°

Gain: 11 dBi

Parameter	Value
Frequency range, GHz	11.7-12.7 (or other 800 MHz of Ku-band using "customized equipment" button)
Gain, dBi, at least	11
<b>Gain variation in the aperture</b> , dB, not more	±2
VSWR, max	2
Polarization	horizontal
Cross-polarization, dB, not less	25
HPBW:	

@horizontal	360°
@vertical	10±1°
Input power, W, up to	20
Waveguide	WR-75 flange
Operating temperature, ° C	-40 +80
Humidity	100% @ 25°C
Dimensions, mm, not more	245x115x115
Weight, kg, not more	2.5
Mount	Mounting on a vertical pipe with a diameter of 40 mm (max)
Casing material	dust/moisture proof

Taking into consideration that we (UMT LLC) are developer and system integrator, also do not stop on our technical growth and improvement, know that view of all our devices and equipment including their technical parameters may be different from pictures presented on website and parameters

listed on each device webpage.

**Note!** All details customer has to confirm in advance during ordering and before payment. Those parameters that were not specified and / or were not agreed while ordering will be implemented as basic at the discretion of the manufacturer. Each our customer has 1.5 year warranty and 7 year aftersales support for whole range of our products.