

## SWA-X360 V2 7.0-7.5 GHZ



SWA-X360 v2 7.0-7.5 GHz is omni Slotted Waveguide Antenna

It is designed for X-band with antenna aperture of 360° and linear polarization

Frequency range of 7.0-7.5 GHz (or any other of X-band)

Beam (H): 360°; Beam (V): 10°

Gain (min): 7.75 dBi

Parameter	Value
<b>Frequency range, GHz</b>	7.0 – 7.5 (or choose other range of X-band via “customized” button)
<b>Gain, dBi, at least</b>	7.75
<b>Gain variation in the aperture, dB, not more</b>	±2
<b>VSWR, max</b>	2
<b>Polarization</b>	horizontal (or by order via “customized” button)
<b>Cross-polarization, dB, not less</b>	25
<b>HPBW:</b>	

<b>@horizontal</b>	360°
<b>@vertical</b>	20.6±0.5°
<b>Input power, W, up to</b>	20
<b>Waveguide</b>	WR-112
<b>Type of input connector (by order)</b>	N, female (coax-to-waveguide adapter by order)
<b>Operating temperature, ° C</b>	-40 ... +80
<b>Humidity</b>	100% @ 25°C
<b>Dimensions, mm, not more</b>	245x115x115
<b>Weight, kg, not more</b>	2.5
<b>Mount</b>	Mounting on a vertical pipe with a diameter of 40 mm (max)
<b>Casing material</b>	dust/moisture proof

*Taking into consideration that we (UMT LLC) are developer and system integrator, also do not stop on our technical growth and improvement, know that view of all our devices and equipment including their technical parameters may be different from pictures presented on website and parameters*

*listed on each device webpage.*

**Note!** *All details customer has to confirm in advance during ordering and before payment. Those parameters that were not specified and / or were not agreed while ordering will be implemented as basic at the discretion of the manufacturer. Each our customer has 1.5 year warranty and 7 year aftersales support for whole range of our products.*