KU-BAND SSPB 400 W SOLID STATE POWER BUC (13.75–14.50 GHZ)



Ku-band SSPB 400 W solid-state power BUC covering 13.75–14.50 GHz (Extended Ku) with 80 dB gain and low phase noise.Outdoor GaN-based unit for Ku-band VSAT, teleport, and broadcast uplinks. Psat 57 dBm, LO 13.05 GHz, IF 950–1450 MHz.

RF Characteristics	
Power	400 W
RF Output at Psat	57 dBm
RF Output at Plin	54 dBm
Output Frequency Range	13.75–14.50 GHz (Extended Ku)
Input Frequency Range	950–1450 MHz
Local Oscillator Frequency	13.05 GHz
Output Spurious	-55 dBc max
Spectral Re-growth	-30 dBc @ Plinear
Third order IMD	-25 dBc

Gain & Linearity	
Linear Gain	80 dB Nominal
Gain Control	20 dB in 0.1 dB steps
Gain Stability Over Temp	±2.0 dB max
Gain Variation at fixed temp	±2.0 dB over full band; ±0.5 dB over 40 MHz
Reference & Phase Noise	
10 MHz Reference	0 dBm ±5 dB
Phase Noise	-93 @100 kHz; -103 @1 MHz; -113 @10 MHz
Interfaces	
Input Impedance	50 Ohms
Output VSWR	1.50:1
RF Output Interface	WR75G (Grooved)
IF Input	N-Type Female, 50 Ohms
Connectors	DC: MS3102R14S-9P; AC: MS3102R14S-7P; M&C: MS3112E1419P; Redundancy: MS3112E14-19S (Optional)
Power & Cooling	
Power Consumption (AC)	2400 W
Cooling	Forced Air
Mechanical	

Dimensions (L×W×H)	195 × 406 × 565 mm
Weight	50 kg
Environmental	
Operating Temperature	-40…+55 °C
Storage Temperature	-40…+75 °C
Humidity	0—100% (condensing)
Altitude	10,000 ft ASL

Taking into consideration that we (UMT LLC) are developer and system integrator, also do not stop on our technical growth and improvement, know that view of all our devices and equipment including their technical parameters may be different from pictures presented on website and parameters listed on each device webpage.

Note! All details customer has to confirm in advance during ordering and before payment. Those parameters that were not specified and / or were not agreed while ordering will be implemented as basic at the discretion of the manufacturer. Each our customer has 1.5 year warranty and 7 year aftersales support for whole range of our products.