

STB-UMT-ST265-MINI



STB-UMT-ST265-mini is set-top box (STB, receiver, television decoder) which works in DVB-S, DVB-S2, DVB-T and DVB-T2 standards and supports MPEG-2/MPEG-4/H.264/HEVC/H.265 codecs, also has CA smart card slot.

STB-UMT-ST265-mini :

- AVL2569L chipset Solution with high sensitive tuner
- Fully DVB-S2/T2/ISDB-T and ITU-TJ.83A/B/C compliant
- CVBS/HDMI output supported,USB 2.0 port PVR, multi-media player
- Support MPEG-1,MPEG-2 ,MPEG-4,H.264/HEVC/H.265 HD decoder
- Advanced audio processor supporting Dolby Digital and Dolby Digital Plus(optional)
- USB2.0 host support upgrade ,PVR,timeshifting and media play with U-Flash or HDD
- Frequency Range:55-862MHz

Specification	
DVB-T2 Tuner	
InputFrequency Range	VHF&UHF
Demodulation	COFDM(QPSK/QAM16/QAM64) ,Supports all five QAM modes: 16/32/64/128QAM, and 256 QAM
Bandwidth	Bandwidth 7,8
RF output Connector	(bypass)IEC 169-2 Male

Loop through	177.5-226.5MHz(VHF),474-858 MHz(UHF)
DVB-S2 Tuner	
InputFrequency	950 to 2150Mhz
Input level	-79 to-11dbm
Symbol Rate	1 to 45M
In put impedance	75
DVB-S2 Demodulation	
Wave from	64/16/4QAM
Demodulation	QPSK,8PSK,16APSK,32APSK
Rate	1/2,2/3,3/4,5/6,7/8,8/9,9/10
System Resources	
SDRAM memory	1GBit
FLASH memory	64MBit Flash
Video Decoder	
Standard	ISO/IEC 13818-2 and ISO/IEC 14496-10
Transport stream	ISO/IEC 13818-1
Video decoding	HEVC/H.265,MPEG-4 H.264/AVC SD/HD,MPEG-2 SD/HD (MP@ML and MP@HL),
	JPEG,BMP,PNG, Motion JPEG
	AVI, VOB, MOV, MKV
Video Resolution	480i, 480p, 576i, 576p, 720p, 1080i, 1080p

Aspect ratio	4:3, 16:9 Auto
Audio Decoder	
Standard	MPEG-1 ,MPEG-2(Layer I & II),MP3,AAC-LC 5.1, HE-AAC v1/v2,AC-3(optional), E-AC-3(optional)
Sample rate	32, 44.1, 48
Software	
EPG	yes
Teletext Support	yes
DVB Subtitle	yes
LCN Support (Nordig v1)	yes
Automatic NIT Search start with S21 (306 Mhz)	yes
Option to enable disable LCN support in the Menu	yes
FTE/Scrambled Channel Selection in the Menu	yes
OTA via Cable (DSM-CC) and USB	No
Fav List	yes
Multi Language User Interface incl. German, English, ...	yes
Front Panel	
Led display	yes(optional)

bi-colored LED	Red / Green to indicate the various states of the STB
smart card	No, One SmartCard Slot
Front panel keyboard	3
Infra-red receiver	yes
Rear Panel	
LNB IN	IEC169-2 Female
ANT IN	ISO/IEC 13818-1
Video& Audio R/L	RCA
USB	USB2.0 interface*2pcs
LAN	1
Accessories	
Remote control unit	IR 38kHz NEC
Led display	1pcs
User Manual	1 in English
RCA cable	1(Optional)
HDMI Cable	1(Optional)
Power	
DC INPUT	12V/1A
Power consumption	Max 12W
Physical	
Operating Temperature	0 ~ 45 °C

Taking into consideration that we (UMT LLC) are developer and system integrator, also do not stop on our technical growth and improvement, know that view of all our devices and equipment including their technical parameters may be different from pictures presented on website and parameters listed on each device webpage.

Note! All details customer has to confirm in advance during ordering and before payment. Those parameters that were not specified and / or were not agreed while ordering will be implemented as basic at the discretion of the manufacturer. Each our customer has 1.5 year warranty and 7 year aftersales support for whole range of our products.