

X-BAND SSPB 100 W 7.9-8.4 GHZ SOLID STATE POWER BUC

High power X-band SSPB 100 W transmitter with 70 dB gain, 7.9-8.4 GHz output, LO 6.95 GHz and IF 950-1450 MHz. Compact outdoor ODU with forced air cooling for VSAT hubs, gateways and teleport stations.

RF Characteristics	
Power	100 W
RF Output at P	51.7 dBm
RF Output at P	48.7 dBm
Frequency Band	Lower X
Output Frequency Range	7.9–8.4 GHz
Input Frequency Range	950–1450 MHz
Local Oscillator Frequency	6.95 GHz
Output Spurious	-55 dBc max
Spectral Re-growth	-30 dBc @ Plinear
Third Order IMD	-25 dBc

Gain & Linearity	
Linear Gain	70 dB Nominal
Gain Control	20 dB in 0.1 dB steps
Gain Stability Over Temp	±2.0 dB max

\sim .	. ,		
Gain	Variation	at fixed	temp

 ± 2.0 dB over full band; ± 0.5 dB over 40 MHz

Reference & Phase Noise	
10 MHz Reference	O dBm ±5 dB
Phase Noise	-63 dBc/Hz @100 Hz; -73 dBc/Hz @1 kHz

Interfaces	
Input Impedance	50 Ohms
Output VSWR	1.50:1
RF Output Interface	CPR 112G (Grooved)
IF Input	N-Type Female, 50 Ohms
Connectors	DC: MS3102R14S-9P;
	AC: MS3102R14S-7P;
	M&C: MS3112E1419P;
	Redundancy: MS3112E14-19S (Optional)

Power	
Power Consumption (AC)	900 W
Cooling	Forced Air

Mechanical Mechanical	
Dimensions (L×W×H)	187 × 197 × 317 mm

Weight	13.6 kg
--------	---------

Environmental	
Operating Temperature	-40+55 °C
Storage Temperature	-40+75 °C
Humidity	0–100% (condensing)
Altitude	10,000 ft ASL

Taking into consideration that we (UMT LLC) are developer and system integrator, also do not stop on our technical growth and improvement, know that view of all our devices and equipment including their technical parameters may be different from pictures presented on website and parameters listed on each device webpage.

Note! All details customer has to confirm in advance during ordering and before payment. Those parameters that were not specified and / or were not agreed while ordering will be implemented as basic at the discretion of the manufacturer. Each our customer has 1.5 year warranty and 7 year aftersales support for whole range of our products.